


MEDIDAS ROSCAS (mm)

ROSCA MACHO BSP




ROSCA BSP CÓNICA		
ROSCA	ACCESFLUID	Ø D
1/8"	01	9,7
1/4"	02	13,2
3/8"	03	16,7
1/2"	04	21,0
3/4"	05	26,4
1"	06	33,2
1 1/4"	07	42,0
1 1/2"	08	47,8
1 3/4"	-	53,7
2"	09	59,6
2 1/2"	10	75,2
3"	11	87,9
4"	12	113,0

ROSCA NPT	
ROSCA	Ø D
1/8"	9,5
1/4"	12,5
3/8"	15,9
1/2"	19,8
3/4"	25,1
1"	31,5
1 1/4"	40,2
1 1/2"	46,3

ROSCA MÉTRICA	
ROSCA	Ø D
M6X1,0	6,0
M8X1,0	8,0
M10X1,0	10,0
M12X1,0	12,0
M12X1,5	12,0
M14X1,0	14,0
M14X1,5	14,0
M16X1,0	16,0
M16X1,5	16,0
M18X1,0	18,0
M18X1,5	18,0
M20X1,5	20,0
M22X1,5	22,0

ROSCA HEMBRA BSP



ROSCA	ACCESFLUID	Ø D
1/8"	01	8,6
1/4"	02	11,4
3/8"	03	15,0
1/2"	04	18,6
3/4"	05	24,1
1"	06	30,3
1 1/4"	07	39,0
1 1/2"	08	44,8
1 3/4"	-----	50,8
2"	09	56,7
2 1/2"	10	72,2
3"	11	84,9
4"	12	110,1

ROSCA	Ø D
1/8"	9,1
1/4"	11,9
3/8"	15,3
1/2"	18,9
3/4"	24,2
1"	30,4
1 1/4"	39,1
1 1/2"	45,1

ROSCA	Ø D
M6X1,0	5,2
M8X1,0	6,9
M10X1,0	8,9
M12X1,0	10,9
M12X1,5	10,4
M14X1,0	12,9
M14X1,5	12,4
M16X1,0	14,9
M16X1,5	14,4
M18X1,0	16,9
M18X1,5	16,4
M20X1,5	18,4
M22X1,5	20,4

CONVERSION PULG/MM

PULGADAS	MM	PULGADAS	MM	PULGADAS	MM
1/32	0,79	7/16	11,11	1-1/4	31,75
1/16	1,59	1/2	12,70	1-1/2	38,10
3/32	2,38	9/16	12,03	1-3/4	44,45
1/8	3,18	5/8	15,88	2	50,80
5/32	3,97	11/16	17,46	2-1/4	57,15
3/16	4,76	3/4	19,05	2-1/2	63,50
1/4	6,35	7/8	22,23	3	76,20
5/16	7,94	1	25,40	4	101,60
3/8	9,53	1-1/8	28,58	6	152,40

CONVERSIONES

PRESIÓN	CAUDAL AGUA	TEMPERATURA
De BAR a PSI → bar x 14,5	De Kv (m3/h) a Cv (galones/minuto) → x 1,1158	De °C a °Fahrenheit → (1.8 x °C) + 32
De PSI a BAR → psi / 14,5	De Cv (galones/minuto) a Kv (m3/h) → x 984	De °Fahrenheit a °C → 0.555 (°F - 32)